




No.of CKTS	A	B	C
04	3.75	6.25	8.55
05	5.00	7.50	9.80
06	6.25	8.75	11.05
07	7.50	10.00	12.30
08	8.75	11.25	13.55
09	10.00	12.50	14.80
10	11.25	13.75	16.05
11	12.50	15.00	17.30
12	13.75	16.25	18.55
13	15.00	17.50	19.80
14	16.25	18.75	21.05
15	17.50	20.00	22.30
16	18.75	21.25	23.55
17	20.00	22.50	24.80
18	21.25	23.75	26.05
19	22.50	25.00	27.30
20	23.75	26.25	28.55
21	25.00	27.50	29.80
22	26.25	28.75	31.05
23	27.50	30.00	32.30
24	28.75	31.25	33.55
25	30.00	32.50	34.80
26	31.25	33.75	36.05
27	32.50	35.00	37.30
28	33.75	36.25	38.55
29	35.00	37.50	39.80
30	36.25	38.75	41.05
31	37.50	40.00	42.30
32	38.75	41.25	43.55
33	40.00	42.50	44.80
34	41.25	43.75	46.05
35	42.50	45.00	47.30


Specifications:
 Rating:
 Current Rating:0.4 Amp
 Voltage Rating:50V AC/DC
 Operating Temperature Range:-20~+80°C
 Max Processing Temp.:260°C for 5 Seconds

Electrical:
 Contact resistance:40m Ohm Max
 Insulator resistance:500M ohm min.
 Withstanding Voltage:200V AC/Minute

Material And Finish:
 Housing:Nylon-46 UL94V-0 Natural
 Terminal:Phosphor Bronze,
 Plating:Tin plated Over Nickel



(Tolerance:0.05)
 FFC/FPC Dimension T=0.3mm



DESCRIPTION(內容):
FPC 1.25mm Right Angle(RoHS)
 PART NO:
 (料號) FPC148N0XX-NTT-CF1337
 DWG NO(圖號): 0012147-XX2321

DRAWN(製圖):
GONG
 CHECKED(確認):
TERESA
 APPROVAL(核准):
JOHNNY

GENERAL TOLERANCE:
 (公差)
 . ± 0.30 . ± 3°
 .0 ± 0.20 .0 ± 2°
 .00 ± 0.10 .00 ± 1°
 .000 ± 0.05
 SCALE(比例):
FREE

REV:
R1
 UNIT:
mm
 SIZE:
A4
 SHEET:
1/1

REV
R0
R1
R2
R3

DESCRIPTION
 變更圖面

DATE
2017.12.21
2024.01.19