



FEATURES

Double tuning fork type contact guarantees high reliability.
 2.54MM pitch Low-Profile mini type Match to 0.64mm sq. posts.

MATERIAL

- Insulator 30% Glass Filled P.B.T. (UL 94V-0)
- Contact Gold Plated
- Terminal 5191 Phosphor Bronze

SPECIFICATIONS

- Current Rating: 3 amperes MAX
- Contact Resistance: 30m Ω MAX
- Insulation Resistance: 1000 Megohms MIN
- Dielectric Withstanding Voltage: AC 650 volts RMS at sea level



DESCRIPTION(內容):	DRAWN(製圖):	GENERAL TOLERANCE:	REV:	REV	DESCRIPTION	DATE
MINI JUMPER 2.54mm Pitch CLOSE TYPE (H=4.6)(RoHS)	GONG	塑膠公差皆為±0.30 金屬公差皆為±0.05	R2	R0		2008.12.02
	CHECKED(確認):		UNIT:	R1	修正Insulation Resistance	2016.04.21
PART NO:	TERESA	SCALE(比例):	mm	R2	變更Ⓐ尺寸(原:0.7)、塑膠公差(原:±0.20)	2017.06.21
(料號) CMJ-45AB	APPROVAL(核准):	FREE	SIZE:	R3		
DWG NO(圖號): YM00818	JOHNNY		A4			
			SHEET:			
			1/1			