



■ MATERIAL

- Insulator: Glass-Fiber P. B. T(UL94V-0)
- Contact: Brass
- Plating: MATING AREA- G/F GOLD OVER NICKEL.
SOLDER AREA- TIN OVER NICKEL.

■ SPECIFICATIONS

- Insulation Resistance: 5000M Ω min at 500 VDC
- Dielectric Withstanding Volatge: 1000 V-AC/1 min
- Current Rating: 3A
- Contact Resistance: 20m Ω max
- Operating Temperature: -55°C to 105°C
- Insartion Force: 340g max per pair
- Withdrawal Force: 28g min per pair

■ DIMENSIONS

Circuits	A	B	C	Circuits	A	B	C	Circuits	A	B	C	Circuits	A	B	C
6	5.08	10.66	14.22	24	27.94	33.52	37.08	42	50.80	56.38	59.94	60	73.66	79.24	82.80
8	7.62	13.20	16.76	26	30.48	36.06	39.62	44	53.34	58.92	62.48	62	76.20	81.78	85.34
10	10.16	15.74	19.30	28	33.02	38.60	42.16	46	55.88	61.46	65.02	64	78.74	84.32	87.88
12	12.70	18.28	21.84	30	35.56	41.14	44.70	48	58.42	64.00	67.56	66	81.28	86.86	90.42
14	15.24	20.82	24.38	32	38.10	43.68	47.24	50	60.96	66.54	70.10	68	83.82	89.40	92.96
16	17.78	23.36	26.92	34	40.64	46.22	49.78	52	63.50	69.08	72.64	70	86.36	91.94	95.50
18	20.32	25.90	29.46	36	43.18	48.76	52.32	54	66.04	71.62	75.18	72	88.90	94.48	98.04
20	22.86	28.44	32.00	38	45.72	51.30	54.86	56	68.58	74.16	77.72				
22	25.40	30.98	34.54	40	48.26	53.84	57.40	58	71.12	76.70	80.26				



DESCRIPTION(內容):
CONNECTOR PITCH 2.54mm FOR PCB DIP
SOLDER RIGHT ANGLE

PART NO:
(料 號) CSA-XXR

DWG NO(圖號): SAXXR

DRAWN(製圖):
mimi

CHECKED(確認):
MANDY

APPROVAL(核准):
JOHNNY

GENERAL TOLERANCE:
(公差)

SCALE(比例):
FREE

REV:
R2

UNIT:
mm

SIZE:
A4

SHEET:
1/1

REV	DESCRIPTION	DATE
R0	RELEASE (RoHS)	2005.11.17 2006.07.05
R1	變更環保章字樣	2006.08.16
R2	PIN 變更尺寸: 0.6→0.65 補充 MATERIAL PLATING 說明&公差	2008.12.03
R3		