



SPECIFICATION:
 PITCH BETWEEN POLES : 2.0mm
 CURRENT RATING : 2A AC/DC(max.)
 VOLTAGE RATING : 250V AC/DC
 CONTACT RESISTANCE : INITIAL VALUE/10mΩ max.
 AFTER ENVIRONMENTAL TESTING/20mΩ max.
 INSULATION RESISTANCE : 1000MΩ (min.)
 WITHSTAND VOLTAGE : 800V AC/MINUTE
 TEMPERATURE RANGE : -25°C TO +85°C
FEATURES:
 MATERIAL : NYLON 66 UL94V-0



ORDER INFORMATION:

有凸點:CMI-H200-2xXXT
 無凸點:CMI-H200-2xXX

Dimensional and Order information

Poles	DIM:(mm)		Poles	DIM:(mm)	
	A	B		A	B
2x02	2.00	4.3	2x15	28.00	30.3
2x03	4.00	6.3	2x16	30.00	32.3
2x04	6.00	8.3	2x17	32.00	34.3
2x05	8.00	10.3	2x18	34.00	36.3
2x06	10.00	12.3	2x19	36.00	38.3
2x07	12.00	14.3	2x20	38.00	40.3
2x08	14.00	16.3	2x21	40.00	42.3
2x09	16.00	18.3	2x22	42.00	44.3
2x10	18.00	20.3	2x23	44.00	46.3
2x11	20.00	22.3	2x24	46.00	48.3
2x12	22.00	24.3	2x25	48.00	50.3
2x13	24.00	26.3	2x30	58.00	60.3
2x14	26.00	28.3			



DESCRIPTION(內容):
 杜邦 2.0mm 雙排 HOUSING (RoHS)

PART NO:
 (料號) CMI-H200-2xXX _
 DWG NO(圖號): 2000-H-2X

DRAWN(製圖):
 GONG
 CHECKED(確認):
 TERESA
 APPROVAL(核准):
 JOHNNY

GENERAL TOLERANCE:
 (公差)
 .00 :±0.15
 .0 :±0.25
 SCALE(比例):
 FREE

REV:
 R3
 UNIT:
 mm
 SIZE:
 A4
 SHEET:
 1/1

REV	DESCRIPTION	DATE
R0	修改接觸阻抗單位	2006.11.18
R1	2007年圖面版本更新	2007.07.30
R2	圖面更新	2012.05.31
R3	圖面更新	2016.06.04